



SIMATIC S7-1200, analog I/O SM 1234, 4 AI/2 AO, +/-10 V, 14-bit resolution or 0 (4)-20mA, 13-bit resolution

General information	
Product type designation	SM 1234, AI 4x13 bit/AQ 2x14 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	60 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	4; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	625 µs
Input ranges	
• Voltage	Yes; ±10V, ±5V, ±2.5V
• Current	Yes; 4 to 20 mA, 0 to 20 mA
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	≥9 MOhm
• -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	≥9 MOhm
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	≥9 MOhm
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	280 Ω
• 4 mA to 20 mA	Yes
Analog outputs	
Number of analog outputs	2; Current or voltage
Output ranges, voltage	
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• 4 mA to 20 mA	Yes

Load impedance (in rated range of output)	
• with voltage outputs, min.	1 000 Ω
• with current outputs, max.	600 Ω
Cable length	
• shielded, max.	100 m; shielded, twisted pair
Analog value generation for the inputs	
Measurement principle	Differential
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit; + sign
• Integration time, parameterizable	Yes
• Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz
Smoothing of measured values	
• parameterizable	Yes
• Step: None	Yes
• Step: low	Yes
• Step: Medium	Yes
• Step: High	Yes
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; Voltage: 14 bit; Current : 13 bit
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C $\pm 0.1\%$, to 55 °C $\pm 0.2\%$ total measurement range
Temperature error (relative to output range), (+/-)	25 °C $\pm 0.3\%$, to 55 °C $\pm 0.6\%$ total measurement range
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.1 %
• Voltage, relative to output range, (+/-)	0.3 %
• Current, relative to output range, (+/-)	0.3 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
• Common mode voltage, max.	12 V
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• for status of the inputs	Yes
• for status of the outputs	Yes
• for maintenance	Yes
Potential separation	
Potential separation analog outputs	
• between the channels and the power supply of the electronics	No
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ecological footprint	
• environmental product declaration	Yes

Global warming potential																																								
— global warming potential, (total) [CO2 eq]	43.1 kg																																							
— global warming potential, (during production) [CO2 eq]	7.62 kg																																							
— global warming potential, (during operation) [CO2 eq]	36 kg																																							
— global warming potential, (after end of life cycle) [CO2 eq]	-0.544 kg																																							
Ambient conditions																																								
Free fall																																								
• Fall height, max.	0.3 m; five times, in product package																																							
Ambient temperature during operation																																								
• min.	-20 °C																																							
• max.	60 °C																																							
• horizontal installation, min.	-20 °C																																							
• horizontal installation, max.	60 °C																																							
• vertical installation, min.	-20 °C																																							
• vertical installation, max.	50 °C																																							
Ambient temperature during storage/transportation																																								
• min.	-40 °C																																							
• max.	70 °C																																							
Air pressure acc. to IEC 60068-2-13																																								
• Operation, min.	795 hPa																																							
• Operation, max.	1 080 hPa																																							
• Storage/transport, min.	660 hPa																																							
• Storage/transport, max.	1 080 hPa																																							
Relative humidity																																								
• Operation at 25 °C without condensation, max.	95 %																																							
Pollutant concentrations																																								
• SO2 at RH < 60% without condensation	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free																																							
connection method																																								
required front connector	Yes																																							
Mechanics/material																																								
Enclosure material (front)																																								
• Plastic	Yes																																							
Dimensions																																								
Width	45 mm																																							
Height	100 mm																																							
Depth	75 mm																																							
Weights																																								
Weight, approx.	220 g																																							
Classifications																																								
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-01</td></tr><tr><td>ETIM</td><td>9</td><td>EC001420</td></tr><tr><td>ETIM</td><td>8</td><td>EC001420</td></tr><tr><td>ETIM</td><td>7</td><td>EC001420</td></tr><tr><td>IDEA</td><td>4</td><td>3562</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	14	27-24-22-01	eClass	12	27-24-22-01	eClass	9.1	27-24-22-01	eClass	9	27-24-22-01	eClass	8	27-24-22-01	eClass	7.1	27-24-22-01	eClass	6	27-24-22-01	ETIM	9	EC001420	ETIM	8	EC001420	ETIM	7	EC001420	IDEA	4	3562	UNSPSC	15	32-15-17-05
	Version	Classification																																						
eClass	14	27-24-22-01																																						
eClass	12	27-24-22-01																																						
eClass	9.1	27-24-22-01																																						
eClass	9	27-24-22-01																																						
eClass	8	27-24-22-01																																						
eClass	7.1	27-24-22-01																																						
eClass	6	27-24-22-01																																						
ETIM	9	EC001420																																						
ETIM	8	EC001420																																						
ETIM	7	EC001420																																						
IDEA	4	3562																																						
UNSPSC	15	32-15-17-05																																						
Approvals / Certificates																																								
General Product Approval																																								



[Manufacturer Declaration](#)



[Metrological Approval](#)



EMV

For use in hazardous locations



[EM](#)



For use in hazardous locations

Marine / Shipping

[CCC-Ex](#)



[NK / Nippon Kaiji Kyokai](#)



Marine / Shipping

Environment



[CCS \(China Classification Society\)](#)



last modified:

10/9/2024