



Figure similar

Article No. : 6SL3120-2TE21-8AA3

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
DC link voltage	DC 510 ... 720 V
Electronics power supply	DC 24 V -15 % / +20 %
Current demand, max.	1.00 A
DC-link current I _d	43.0 A
Output current	
Rated value I _N	2 x 18.0 A
Base load current I _H	2 x 15.3 A
For S6 duty (40%) I _{S6}	2 x 24.0 A
I _{max}	2 x 36.0 A
Type rating ²⁾	
Based on I _N	2 x 9.7 kW
Based on I _H	2 x 8.2 kW
Current carrying capacity	
DC link busbars	100 A
24 V busbars ⁴⁾	20 A
DC link capacitance	705 µF
Ambient conditions	
Installation altitude (without derating)	1,000 m (3,281 ft)
Cooling ⁸⁾	Internal air cooling
Cooling air requirement	0.016 m³/s
Ambient temperature	
During operation	0 ... 40 °C (32 ... 104 °F)

Connections	
Motor end	
Version	connector (X1, X2)
PE connection	M5 screw
Shield connecting kit	Integrated connection plug (X1, X2)
Max. motor cable length	
Shielded	70 m (230 ft)
Unshielded	100 m (328 ft)
Standards	
Compliance with standards	CE, cULus
Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1
Mechanical data	
Line side	
Width	100.00 mm (3.94 in)
Height	380.00 mm (14.96 in)
Depth	270.00 mm (10.63 in)
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	6.8 kg (14.99 lb)
General tech. specifications	
Sound pressure level (1m)	60.0 dB
Power loss, typ./max. ⁹⁾	0.28 kW / 0.35 kW

²⁾Rated output of a typical standard asynchronous motor at 400 V 3 AC

⁴⁾If, when connecting several Line Modules and Motor Modules in series, the current carrying capacity exceeds 20 A, another 24 V DC connection is required using a 24 V terminal adapter (max. connectable cross-section 6 mm², max. protection 20 A).

⁸⁾Power units with intensified air cooling thanks to integrated fan

⁹⁾Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply