



## GT-H10 Sensor Head

(€

\*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

## **Specifications**

Model		GT-H10
Туре		Sensor head: Standard
Measuring range		10 mm
Measuring force	Downward mounting	1.0 N*1
	Side mounting	0.9 N*1
	Upward mounting	0.8 N*1
Mechanical response		10 Hz (at ambient temperature of 23 °C)
Repeatability		3 μm (at ambient temperature of 23 °C)*2
Environmental resistance	Enclosure rating	IP67
	Ambient temperature	-10 to +55 °C
	Relative humidity	35 to 85 % RH
Material		Housing: TYPE430 Stainless steel, Indicator: Polyarylate, Dust boot: NBR, Contact: TYPE304 stainless steel, Cable: PVC
Weight		Approx. 115 g (With 2-m cable)

<sup>\*1</sup> Value read near the center of the measuring range


KEYENCE UK & IRELAND +44(0)1908-696-900 https://www.keyence.co.uk 2025/03/02 Page 1 of 2

<sup>\*2</sup> Value read at the center of the measuring range with the response time set to 100 ms.



## **Dimensions**

\* Download CAD file or product manual for larger image/text and more detail.



GT-H10

