



LR-ZH490CB

M18 threaded mount w/ M12 connector type, 490 mm



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		LR-ZH490CB*1
Type		U.C.D. Function Distance based laser sensor
Shape		M18 Threaded mount
Output		NPN/PNP selectable
Cable connection		M12 connector, 4-pin
Detectable distance		25 to 490 mm (465 to 0)*2
Standard detectable deviation		25 to 170 mm: 9 mm 170 to 290 mm: 25 mm 290 to 390 mm: 40 mm 390 to 490 mm: 50 mm
Display resolution		1 to 5 (1 to 5 mm)
Spot diameter		Approx. ø3 mm
Response time		1.5 ms / 10 ms / 50 ms selectable
Light source	Type	Red laser (660 nm)
	Laser class	Class 2 laser product (IEC60825-1) Class II Laser product (FDA (CDRH) Part1040.10)
Function	Indicator	3-digit 7-segment display (white), output indicator (yellow), DATUM indicator (orange), 1 spot indicator (green)
	Timer	OFF/ON delay/OFF delay/One-shot
Rating	Power voltage	10 to 30 VDC, including 10% ripple (P-P), Class 2 or LPS
	Power consumption	450 mW or less (18 mA or less at 24 V, 34 mA or less at 12 V)
Specifications	Control output	NPN open collector/PNP Open collector selectable, Applied voltage 30 VDC or less, Control current 100 mA or less, Residual voltage 1.2 V or less at 10 mA or less, 2 V or less at 10 to 100 mA
	Protection circuit	Protection against reverse power connection, output overcurrent, output surge, reverse output connection
	Output operation	Light-ON / Dark-ON selectable
	External input	Input time calibration: 35 ms or more ON, 35 ms or more OFF Laser emission stop: 2 ms or more ON, 20 ms or more OFF Short-circuit current NPN: 1 mA or less/PNP: 2 mA or less
Environmental resistance	Enclosure rating	IP68 (IEC60529), IP69K (DIN40050-9), NEMA 4X, 6P, 13 (NEMA250), ECOLAB*3, Diversy*3
	Insulation resistance	20 MΩ or more (500 VDC)
	Ambient light	Incandescent lamp: 10,000 lux or less Sunlight: 20,000 lux or less at 240 mm*4 Incandescent lamp: 2,000 lux or less Sunlight: 4,000 lux or less at 490 mm*4
	Ambient temperature	-10 to +50 °C (No freezing)

	Relative humidity	35 to 85 % RH (No condensation)
	Storage temperature	-25 to +75 °C (No freezing)
	Withstand voltage	1,000 VAC, 50/60 Hz, 1 min
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm, 2 hours in each of the X, Y, and Z directions
	Shock resistance	1,000 m/s ² , 6 times in each of the X, Y, and Z directions
Material		Case: SUS316L, Display: PES, Lens cover: PMMA with scratch-resistant coating, Packing/Connector ring: FKM, Nut: SUS316L, Lock washer: SUS304
Accessories		Instruction Manual, FDA warning/certification/identification label, Laser warning/explanation labels
Weight		Approx. 75 g

*1 IO-Link specification v.1.1/COM2 (38.4 kbps) is supported. (LR-ZH490CB : Only when PNP output is selected.) You can download a setup file from the KEYENCE website. If using the product in an environment in which downloading files over the internet is not possible, contact your nearest KEYENCE office.

*2 Display readings can be used as a guide for the detecting distance. When the setting value is tuned, the readout shifts. When the value exceeds "-99", "-FF" is displayed.

*3 Have passed resistance tests with cleaning agents from multiple manufactures.

*4 When the response time is 10 ms

* Download CAD file or product manual for larger image/text and more detail.

[illegible]