



SR-UR1

USB Communication Unit



*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		SR-UR1
Operating System		Windows 10 Pro or later, 32 bit/64 bit Windows 8 Pro or later, 32 bit/64 bit (excluding Windows RT) Windows 7 Professional or later, 32 bit/64 bit
Code reader power supply		5 VDC + 5%, – 15% (peak: 700 mA)
Display LEDs		4 (status display, POWER, SD, RD)
Head interface	Connector	1 (D-sub 9-pin connector)
	Communication standard	RS-232C compliant
	Communication speed	9600, 19200, 38400, 57600, 115200 bps
	Data bit length	7/8 bits
	Parity check	None/even/odd
	Stop bit length	1/2 bits
USB	Connector	1 (Mini-B)
	Communication standard	USB 2.0 Full Speed
	Interface	USB-COM, USB keyboard
Rating	Voltage	4.5 to 5.25 V
	Current consumption	500 mA
Environmental resistance	Ambient temperature	–20 to +50°C
	Relative humidity	20 to 95%RH (no condensation)
	Storage temperature	–20 to +60°C
	Storage relative humidity	20 to 95%RH (no condensation)
	Operating environment	No dust or corrosive gas present
Dimensions		67 × 86 × 33 mm
Weight		Approx. 100 g

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

SR-UR1

