

variable speed drive - 22kW- 400V - 3 phases - ATV340 Ethernet

Local distributor code:

408900634 ATV340D22N4E

EAN Code: 3606480967085

Main

Range of product	Altivar Machine ATV340
Product or component type	Variable speed drive
Product specific application	Machine
Mounting mode	Cabinet mount
Variant	Standard version
Communication port protocol	Modbus TCP EtherNet/IP Modbus serial
Network number of phases	3 phases
Supply frequency	5060 Hz +/- 5 %
[Us] rated supply voltage	380480 V - 1510 %
Nominal output current	46.0 A
Motor power kW	30 kW for normal duty 22 kW for heavy duty
Motor power hp	40 hp for normal duty 30 hp for heavy duty
EMC filter	Class C3 EMC filter integrated
IP degree of protection	IP20

Complementary

Discrete input number	5		
Discrete input type	PTI programmable as pulse input: 030 kHz, 24 V DC (30 V) DI1DI5 safe torque off, 24 V DC (30 V), impedance: 3.5 kOhm programmable		
number of preset speeds	16 preset speeds		
Discrete output number	2.0		
Discrete output type	Programmable output DQ1, DQ2 30 V DC 100 mA		
Analogue input number	2		
Analogue input type	Al1 software-configurable current: 020 mA, impedance: 250 Ohm, resolution 12 bits Al1 software-configurable temperature probe or water level sensor Al1 software-configurable voltage: 010 V DC, impedance: 31.5 kOhm, resolution 12 bits Al2 software-configurable voltage: - 1010 V DC, impedance: 31.5 kOhm, resolution 12 bits		
Analogue output number	1		

Analogue output type	Software configurable voltage AO1: 0 40 V DC impedance 470 Ohm resolution 40	
Analogue output type	Software-configurable voltage AQ1: 010 V DC impedance 470 Ohm, resolution 10 bits Software-configurable current AQ1: 020 mA impedance 500 Ohm, resolution 10 bits	
Relay output number	2	
Output voltage	<= power supply voltage	
Relay output type	Relay outputs R1A Relay outputs R1C electrical durability 100000 cycles Relay outputs R2A Relay outputs R2C electrical durability 100000 cycles	
Maximum switching current	Relay output R1C on resistive load, cos phi = 1: 3 A at 250 V AC Relay output R1C on resistive load, cos phi = 1: 3 A at 30 V DC Relay output R1C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R1C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V DC Relay output R2C on resistive load, cos phi = 1: 5 A at 250 V AC Relay output R2C on resistive load, cos phi = 1: 5 A at 30 V DC Relay output R2C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R2C on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V DC	
Minimum switching current	Relay output R1B: 5 mA at 24 V DC Relay output R2C: 5 mA at 24 V DC	
Physical interface	2-wire RS 485	
Connector type	3 RJ45	
Method of access	Slave Modbus RTU Slave Modbus TCP	
Transmission rate	4.8 kbit/s 9.6 kbit/s 19.2 kbit/s 38.4 kbit/s	
Transmission frame	RTU	
Number of addresses	1247	
Data format	8 bits, configurable odd, even or no parity	
Type of polarization	No impedance	
4 quadrant operation possible	True	
Asynchronous motor control profile	Optimized torque mode Constant torque standard Variable torque standard	
Synchronous motor control profile	Permanent magnet motor Reluctance motor	
Pollution degree	2 conforming to IEC 61800-5-1	
Maximum output frequency	0.599 kHz	
Acceleration and deceleration ramps	S, U or customized Linear adjustable separately from 0.019999 s	
Motor slip compensation	Automatic whatever the load Can be suppressed Adjustable Not available in permanent magnet motor law	
Switching frequency	216 kHz adjustable 616 kHz with derating factor	
Nominal switching frequency	4 kHz	
Braking to standstill	By DC injection	
Brake chopper integrated	True	
Line current	60.1 A at 380 V (normal duty) 48.6 A at 480 V (normal duty) 63.5 A at 380 V (heavy duty) 50.6 A at 480 V (heavy duty)	

Line current	63.5 A at 380 V without line choke (heavy duty) 50.5 A at 480 V without line choke (heavy duty)	
	67.9 A at 480 V with external line choke (normal duty)	
	54.4 A at 380 V with external line choke (heavy duty)	
	64.1 A at 480 V with external line choke (heavy duty)	
	50.8 A at 380 V with external line choke (normal duty)	
Maximum input current	63.5 A	
Maximum output voltage	480 V	
Apparent power	45.1 kVA at 480 V (normal duty)	
	42.1 kVA at 480 V (heavy duty)	
Maximum transient current	68.2 A during 60 s (normal duty)	
	69 A during 60 s (heavy duty)	
	83.7 A during 2 s (normal duty)	
	83 A during 2 s (heavy duty)	
Electrical connection	Screw terminal, clamping capacity: 0.22.5 mm² for control	
	Screw terminal, clamping capacity: 625 mm² for motor Screw terminal, clamping capacity: 1025 mm² for line side	
	Screw terminal, clamping capacity: 1025 mm² for DC bus	
Prospective line Isc	22 kA	
Base load current at high overload	46.0 A	
Base load current at low overload	62.0 A	
Power dissipation in W	Natural convection: 28 W at 380 V, switching frequency 4 kHz (heavy duty) Forced convection: 486 W at 380 V, switching frequency 4 kHz (heavy duty)	
	Natural convection: 39 W at 380 V, switching frequency 4 kHz (normal duty)	
	Forced convection: 631 W at 380 V, switching frequency 4 kHz (normal duty)	
Electrical connection	Control: screw terminal 0.22.5 mm²/AWG 24AWG 12	
	Motor: screw terminal 625 mm²/AWG 8AWG 3	
	Line side: screw terminal 1025 mm²/AWG 6AWG 3 DC bus: screw terminal 1025 mm²/AWG 6AWG 3	
With safety function Safely Limited Speed (SLS)	True	
With safety function Safe brake management (SBC/SBT)	True	
With safety function Safe Operating Stop (SOS)	False	
With safety function Safe Position (SP)	False	
With safety function Safe programmable logic	False	
With safety function Safe Speed Monitor (SSM)	False	
With safety function Safe Stop 1 (SS1)	True	
With sft fct Safe Stop 2 (SS2)	False	
With safety function Safe torque off (STO)	True	
With safety function Safely Limited Position (SLP)	False	
With safety function Safe Direction (SDI)	False	

Protection type	Thermal protection: motor		
	Safe torque off: motor		
	Motor phase loss: motor		
	Thermal protection: drive		
	Safe torque off: drive		
	Overheating: drive		
	Overcurrent: drive		
	Output overcurrent between motor phase and earth: drive		
	Output overcurrent between motor phases: drive		
	Short-circuit between motor phase and earth: drive		
	Short-circuit between motor phases: drive		
	Motor phase loss: drive		
	DC Bus overvoltage: drive		
	Line supply overvoltage: drive		
	Line supply undervoltage: drive		
	Input supply loss: drive		
	Exceeding limit speed: drive		
	Break on the control circuit: drive		
Width	180.0 mm		
Height	385.0 mm		
Depth	249.0 mm		
Net weight	10.2 kg		
Continuous output current	62 A at 4 kHz for normal duty		
	46 A at 4 kHz for heavy duty		

Environment

Operating altitude	<= 3000 m with current derating above 1000m	
Operating position	Vertical +/- 10 degree	
Product certifications	UL CSA TÜV EAC CTick	
Marking	CE	
Standards	IEC 61800-3 IEC 61800-5-1 IEC 60721-3 IEC 61508 IEC 13849-1 UL 618000-5-1 UL 508C	
Assembly style	With heat sink	
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6	
Environmental class (during operation)	Class 3C3 according to IEC 60721-3-3 Class 3S3 according to IEC 60721-3-3	
Maximum acceleration under shock impact (during operation)	70 m/s² at 22 ms	
Maximum acceleration under vibrational stress (during operation)	5 m/s² at 9200 Hz	
Maximum deflection under vibratory load (during operation)	1.5 mm at 29 Hz	
Permitted relative humidity (during operation)	Class 3K5 according to EN 60721-3	
Volume of cooling air	128.0 m3/h	
type of cooling	Forced convection	
Overvoltage category	Class III	

Regulation loop	Adjustable PID regulator	
Noise level	56.7 dB	
pollution degree	2	
Ambient air transport temperature	-4070 °C	
Ambient air temperature for operation	-1550 °C without derating (vertical position) 5060 °C with derating factor (vertical position)	
Ambient air temperature for storage	-4070 °C	
Isolation	Between power and control terminals	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.800 cm
Package 1 Width	54.800 cm
Package 1 Length	33.700 cm
Package 1 Weight	11.890 kg
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	36.780 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	15608
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
Product contributes to saved and avoided emissions	Yes

Use Again


○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No

ATV340D22N4E

Dimensions Drawings

Dimensions


Views: Front - Left - Rear




ATV340D22N4E

Mounting and Clearance

Clearance





Dimensions in mm


X1	X2	X3
≥ 100	≥ 100	≥ 60

Dimensions in in.

X1	X2	X3
≥ 3.94	≥ 3.94	≥ _{2.36}


Mounting Types

Mounting Type A: Side by Side IP20



Possible, at ambient temperature ≤ 50 °C (122 °F)

Mounting Type B: Individual IP20




a 50 mm (1.97 in.) from 50...60°C, no restriction below 50°C

Connections and Schema

Connections and Schema

Three-phase Power Supply with Upstream Breaking via Line Contactor Without Safety Function STO

Connection diagrams conforming to standards ISO13849 category 1 and IEC/EN 61508 capacity SIL1, stopping category 0 in accordance with standard IEC/EN 60204-1.



(1) Use relay output R1 set to operating state Fault to switch Off the product once an error is detected.

A1: Drive


KM1: Line Contactor
Q2, Q3: Circuit breakers

S1: PushbuttonS2: Emergency stop

T1: Transformer for control part

Three-phase Power Supply With Downstream Breaking via Switch Disconnector

ATV340D22N4E




(1) Use relay output R1 set to operating state Fault to switch Off the product once an error is detected.

A1: Drive


Q1: Switch disconnector

Sensor Connection



It is possible to connect either 1 or 3 sensors on terminals Al1.

Control Block Wiring Diagram




- (1) 24V supply (STO)
- (2) STO Safe Torque Off
- (3) PTI Pulse Train In
- (4) PTO Pulse Train Out
- (5) Motor Encoder connection
- (6) Digital outputs
- (7) Digital inputs
- (8) Analog output
- (9) Analog input
- (10) Differential Analog Input
- (11) Ethernet port (only on Ethernet drive version)

SW1: Sink/Source switch R1A, R1B, R1C: Fault relay

R2A, R2C: Sequence relay

Digital Inputs Wiring


Digital Inputs: Internal Supply



In SRC position DISUP outputs 24 V. In SK position DISUP is connected to 0 V.

Digital Inputs: External Supply

Positive Logic, Source, European Style




Negative Logic, Sink, Asian Style | S

Digital Inputs: Internal supply Negative Logic, Sink, Asian Style

Product datasheet


ATV340D22N4E



Digital Outputs Wiring


Digital Outputs: Internal Supply

Positive Logic, Source, European Style, DQCOM to +24V



(1) Relay or valve


Negative Logic, Sink, Asian Style, DQCOM to 0V



(1) Relay or valve

Digital Outputs: External Supply

Positive Logic, Source, European Style, DQCOM to +24V




(1) Relay or valve

Negative Logic, Sink, Asian Style, DQCOM to 0V

Product datasheet

ATV340D22N4E




(1) Relay or valve

Product datasheet

ATV340D22N4E


Performance Curves

Open Loop Applications



- 1: Self-cooled motor: continuous useful torque
- 2: Force-cooled motor: continuous useful torque
- 3: Overtorque for 60 s maximum
- 4: Transient overtorque for 2 s maximum
- 5: Torque in overspeed at constant power

Closed Loop Applications



- 1: Self-cooled motor: continuous useful torque
- 2: Force-cooled motor: continuous useful torque
- 3: Overtorque for 60 s maximum
- 4: Transient overtorque for 2 s maximum
- 5: Torque in overspeed at constant power