

variable speed drive ATV630 - 110kW/150HP - 380...480V - IP00

Local distributor code:

402705369 ATV630C11N4

EAN Code: 3606480796036

Main

Range of product	Altivar Process ATV600	
Product specific application	Process and utilities	
Product or component type	Variable speed drive	
Variant	Standard version	
Device short name	ATV630	
Communication port protocol	Modbus TCP Ethernet Modbus serial	
[Us] rated supply voltage	380480 V - 1510 %	
[Us] rated supply voltage	380480 V	
Product destination	Asynchronous motors Synchronous motors	
EMC filter	Integrated with 150 m conforming to IEC 61800-3 category C3	
IP degree of protection	IP00 conforming to IEC 61800-5-1 IP00 conforming to IEC 60529 IP21 (with kit VW3A9704) conforming to IEC 61800-5-1 IP21 (with kit VW3A9704) conforming to IEC 60529	
type of cooling	Forced convection	
Supply frequency	5060 Hz - 55 %	
Motor power kW	110 kW (normal duty) 90 kW (heavy duty)	
Motor power hp	150 hp normal duty 125 hp heavy duty	
Line current	201 A at 380 V (normal duty) 165 A at 480 V (normal duty) 170 A at 380 V (heavy duty) 143 A at 480 V (heavy duty)	
Prospective line Isc	50 kA	
Apparent power	121.8 kVA at 480 V (normal duty) 102.6 kVA at 480 V (heavy duty)	
Continuous output current	211 A at 2.5 kHz for normal duty 173 A at 2.5 kHz for heavy duty	
Asynchronous motor control profile	Constant torque standard Optimized torque mode Variable torque standard	
Synchronous motor control profile	Permanent magnet motor Synchronous reluctance motor	
Speed drive output frequency	0.1500 Hz	
Nominal switching frequency	2.5 kHz	

Switching frequency	2.58 kHz with derating factor 28 kHz adjustable	
Safety function	STO (safe torque off) SIL 3	
Discrete input logic	16 preset speeds	
Option card	Slot A: communication module, Profibus DP V1 Slot A: communication module, PROFINET Slot A: communication module, DeviceNet Slot A: communication module, Modbus TCP/EtherNet/IP Slot A: communication module, CANopen daisy chain RJ45 Slot A: communication module, CANopen SUB-D 9 Slot A: communication module, CANopen screw terminals Slot A/slot B: digital and analog I/O extension module Slot A/slot B: output relay extension module Slot A: communication module, Ethernet IP/Modbus TCP/MD-Link Communication module, BACnet MS/TP Communication module, Ethernet Powerlink	

Complementary

Complementary	
Mounting mode	Wall mount
Network number of phases	3 phases
Discrete output number	0
Discrete output type	Relay outputs R1A, R1B, R1C 250 V AC 3000 mA Relay outputs R1A, R1B, R1C 30 V DC 3000 mA Relay outputs R2A, R2C 250 V AC 5000 mA Relay outputs R2A, R2C 30 V DC 5000 mA Relay outputs R3A, R3C 250 V AC 5000 mA Relay outputs R3A, R3C 250 V DC 5000 mA Relay outputs R3A, R3C 30 V DC 5000 mA
Output voltage	<= power supply voltage
Permissible temporary current boost	1.1 x In during 60 s (normal duty) 1.5 x In during 60 s (heavy duty)
Motor slip compensation	Can be suppressed Not available in permanent magnet motor law Automatic whatever the load Adjustable
Acceleration and deceleration ramps	Linear adjustable separately from 0.019999 s
Physical interface	Ethernet 2-wire RS 485
Braking to standstill	By DC injection
Protection type	Thermal protection: motor Safe torque off: motor Motor phase break: motor Thermal protection: drive Safe torque off: drive Overheating: drive Overcurrent between output phases and earth: drive Overload of output voltage: drive Short-circuit protection: drive Motor phase break: drive Overvoltages on the DC bus: drive Line supply overvoltage: drive Line supply undervoltage: drive Line supply phase loss: drive Overspeed: drive Break on the control circuit: drive
Transmission rate	10, 100 Mbits 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps
Frequency resolution	Display unit: 0.1 Hz Analog input: 0.012/50 Hz
Transmission frame	RTU

Electrical connection	Control: removable screw terminals 0.51.5 mm²/AWG 20AWG 16 Line side: screw terminal 2 x 503 x 120 mm²/2 x AWG 1/02 x 300 kcmil Motor: screw terminal 2 x 503 x 120 mm²/2 x AWG 1/02 x 300 kcmil	
Connector type	RJ45 (on the remote graphic terminal) for Ethernet/Modbus TCP RJ45 (on the remote graphic terminal) for Modbus serial	
Data format	8 bits, configurable odd, even or no parity	
Type of polarization	No impedance	
Exchange mode	Half duplex, full duplex, autonegotiation Ethernet/Modbus TCP	
Number of addresses	1247 for Modbus serial	
Method of access	Slave Modbus TCP	
Supply	External supply for digital inputs: 24 V DC (1930 V), <1.25 mA, protection type: overload and short-circuit protection Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC +/- 5 %, <10 mA, protection type: overload and short-circuit protection Internal supply for digital inputs and STO: 24 V DC (2127 V), <200 mA, protection type: overload and short-circuit protection	
Local signalling	3 LEDs for local diagnostic 3 LEDs (dual colour) for embedded communication status 4 LEDs (dual colour) for communication module status 1 LED (red) for presence of voltage	
Width	320 mm	
Height	852 mm	
Depth	390 mm	
Net weight	82 kg	
Analogue input number	3	
Analogue input type	Al1, Al2, Al3 software-configurable voltage: 010 V DC, impedance: 31.5 kOhm, resolution 12 bits Al1, Al2, Al3 software-configurable current: 020 mA, impedance: 250 Ohm, resolution 12 bits Al2 voltage analog input: - 1010 V DC, impedance: 31.5 kOhm, resolution 12 bits	
Discrete input number	8	
Discrete input type	DI7, DI8 programmable as pulse input: 030 kHz, 24 V DC (<= 30 V)	
Input compatibility	DI1DI6: discrete input level 1 PLC conforming to IEC 61131-2 DI5, DI6: discrete input level 1 PLC conforming to IEC 65A-68 STOA, STOB: discrete input level 1 PLC conforming to IEC 61131-2	
Discrete input logic	Positive logic (source) (DI1DI8), < 5 V (state 0), > 11 V (state 1) Negative logic (sink) (DI1DI8), > 16 V (state 0), < 10 V (state 1)	
Analogue output number	2	
Analogue output type Software-configurable voltage AQ1, AQ2: 010 V DC impedance 470 Of resolution 10 bits Software-configurable current AQ1, AQ2: 020 mA, resolution 10 bits Software-configurable current DQ-, DQ+: 30 V DC Software-configurable current DQ-, DQ+: 100 mA		
Sampling duration	2 ms +/- 0.5 ms (DI1DI4) - discrete input 5 ms +/- 1 ms (DI5, DI6) - discrete input 5 ms +/- 0.1 ms (AI1, AI2, AI3) - analog input 10 ms +/- 1 ms (AO1) - analog output	
Accuracy	+/- 0.6 % Al1, Al2, Al3 for a temperature variation 60 °C analog input +/- 1 % AO1, AO2 for a temperature variation 60 °C analog output	
Linearity error	AI1, AI2, AI3: +/- 0.15 % of maximum value for analog input AO1, AO2: +/- 0.2 % for analog output	
Relay output number	3	
Relay output type	Configurable relay logic R1: fault relay NO/NC electrical durability 100000 cycles Configurable relay logic R2: sequence relay NO electrical durability 100000 cycles Configurable relay logic R3: sequence relay NO electrical durability 100000 cycles	

Refresh time	Relay output (R1, R2, R3): 5 ms (+/- 0.5 ms)	
Minimum switching current Relay output R1, R2, R3: 5 mA at 24 V DC		
Maximum switching current	Relay output R1, R2, R3 on resistive load, cos phi = 1: 3 A at 250 V AC	
	Relay output R1, R2, R3 on resistive load, cos phi = 1: 3 A at 30 V DC	
	Relay output R1, R2, R3 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250	
	V AC	
	Relay output R1, R2, R3 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V	
	DC	
Isolation	Between power and control terminals	
Maximum output frequency	500 kHz	
Maximum input current	201.0 A	
Variable speed drive application	Building - HVAC compressor centrifugal	
selection	Food and beverage processing other application	
	Mining mineral and metal fan	
	Mining mineral and metal pump	
	Oil and gas fan	
	Water and waste water other application	
	Building - HVAC screw compressor	
	Food and beverage processing pump	
	Food and beverage processing fan	
	Food and beverage processing atomization	
	Oil and gas electro submersible pump (ESP)	
	Oil and gas water injection pump	
	Oil and gas jet fuel pump	
	Oil and gas compressor for refinery	
	Water and waste water centrifuge pump	
	Water and waste water positive displacement pump	
	Water and waste water electro submersible pump (ESP)	
	Water and waste water screw pump	
	Water and waste water lobe compressor	
	Water and waste water screw compressor	
	Water and waste water compressor centrifugal	
	Water and waste water fan	
	Water and waste water conveyor	
	Water and waste water mixer	
Motor power range AC-3	110220 kW at 380440 V 3 phases	
	110220 kW at 480500 V 3 phases	
Quantity per set	1	
Enclosure mounting	Wall mounted	
Enclosure mounting Maximum transient current	Wall mounted 232.1 A during 60 s (normal duty)	

Environment

Insulation resistance	> 1 MOhm 500 V DC for 1 minute to earth	
Noise level	69.9 dB conforming to 86/188/EEC	
Power dissipation in W	Forced convection: 2026 W at 380 V, switching frequency 2.5 kHz	
Volume of cooling air	600 m3/h	
Operating position	Vertical +/- 10 degree	
Maximum THDI	<48 % full load conforming to IEC 61000-3-12	
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6	
Pollution degree	2 conforming to IEC 61800-5-1	
Vibration resistance	1.5 mm peak to peak (f= 213 Hz) conforming to IEC 60068-2-6 1 gn (f= 13200 Hz) conforming to IEC 60068-2-6	
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27	

Relative humidity	595 % without condensation conforming to IEC 60068-2-3	
Ambient air temperature for operation	-1550 °C (without derating) 5060 °C (with derating factor)	
Ambient air temperature for storage	-4070 °C	
Operating altitude	<= 1000 m without derating 10004800 m with current derating 1 % per 100 m	
Product certifications	ATEX zone 2/22 ATEX INERIS TÜV CSA UL DNV-GL	
Marking	CE	
Standards	UL 508C IEC 61800-3 IEC 61800-3 environment 1 category C2 EN/IEC 61800-3 environment 2 category C3 IEC 61800-5-1 IEC 61000-3-12 IEC 60721-3 IEC 61508 IEC 13849-1	
Overvoltage category	III	
Regulation loop	Adjustable PID regulator	
Noise level	69.9 dB	
pollution degree	2	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	66.000 cm
Package 1 Width	47.500 cm
Package 1 Length	103.000 cm
Package 1 Weight	88.600 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	80649
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
[☼] Energy efficiency	
Product contributes to saved and avoided emissions	Yes

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Take-back	No	

Product datasheet

ATV630C11N4


Dimensions Drawings

Dimensions


13 Mar 2025

Drives with IP21 Top Cover Right and Front Views






Drives Without IP21 Top Cover Right and Front Views




Product datasheet


ATV630C11N4



Drives with Lower Conduit Box Sold Separately Rear, Front and Left Views




mm in.





Mounting and Clearance


Clearances



X1	X2	X3
≥ 250 mm (10 in.)	≥ 250 mm (10 in.)	≥ 100 mm (3.94 in.)


Mounting Types

Mounting Type A: Individual IP21




a ≥ = 110 mm (4.33 in.)

Mounting Type B: Side by Side IP20 , Only possible at ambient temperature lower than 40 $^{\circ}\text{C}$ (104 $^{\circ}\text{F})$



Mounting Type C: Individual IP20




a ≥ = 110 mm (4.33 in.)

Connections and Schema

Three-Phase Power Supply with Upstream Breaking via Line Contactor

Connection diagrams conforming to standards EN 954-1 category 1 and IEC/EN 61508 capacity SIL1, stopping category 0 in accordance with standard IEC/EN 60204-1



(1) Line choke if used

(2) Use relay R1 set to operating state Fault to switch Off the product once an error is detected.


A1 : Drive

KM1 : Line Contactor Q2, Q3 : Circuit breakers S1, S2 : Pushbuttons

T1: Transformer for control part

Three-Phase Power Supply with Downstream Breaking via Contactor

Connection diagrams conforming to standards EN 954-1 category 1 and IEC/EN 61508 capacity SIL1, stopping category 0 in accordance with standard IEC/EN 60204-1




(1) Line choke if used

(2) Use relay R1 set to operating state Fault to switch Off the product once an error is detected.

A1 : Drive KM1 : Contactor

Control Block Wiring Diagram




- (1) Safe Torque Off
- (2) Analog Output
- (3) Digital Input
- (4) Reference potentiometer
- (5) Analog Input

R1A, R1B, R1C : Fault relay R2A, R2C : Sequence relay R3A, R3C : Sequence relay

Sensor Connection

It is possible to connect either 1 or 3 sensors on terminals Al2 or Al3.




Sink / Source Switch Configuration


The switch is used to adapt the operation of the logic inputs to the technology of the programmable controller outputs.

- Set the switch to Source (factory setting) if using PLC outputs with PNP transistors.
- Set the switch to Ext if using PLC outputs with NPN transistors.


Switch Set to SRC (Source) Position Using the Output Power Supply for the Digital Inputs




Switch Set to SRC (Source) Position and Use of an External Power Supply for the DIs



Switch Set to SK (Sink) Position Using the Output Power Supply for the Digital Inputs



Switch Set to EXT Position Using an External Power Supply for the DIs




Product datasheet

ATV630C11N4

Performance Curves

Derating Curves



40 °C (104 °F) - Mounting type A, B and C 50 °C (122 °F) - Mounting type A and C 60 °C (140 °F) - Mounting type C

In: Nominal Drive Current SF: Switching Frequency