# **Product datasheet**

Specifications



## Circuit breaker, ComPacT NSX160H, 70kA/415VAC, 3 poles, MicroLogic 2.2M trip unit 150A

C16H32M150

### Main

mann		
Range	ComPacT new generation	
product name	ComPacT NSX new generation	
Device short name	NSX160H	
Product or component type	Circuit breaker	
Device application	Motor protection	
Poles description	3P	
Protected poles description	3D	
[In] rated current	150 A at 65 °C	
[Ue] rated operational voltage	690 V AC 50/60 Hz	
Network type	AC	
Network frequency	50/60 Hz	
Suitability for isolation	Yes conforming to EN/IEC 60947-2	
Utilisation category	Category A	
[Icu] rated ultimate short-circuit breaking capacity	it 100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2   70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2   65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2   50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2   35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2   10 kA Icu at 60/690 V AC 50/60 Hz conforming to IEC 60947-2   85 kA Icu at 600 V AC 50/60 Hz conforming to IEC 60947-2   85 kA Icu at 600 V AC 50/60 Hz conforming to IEC 60947-2   85 kA Icu at 480 V AC 50/60 Hz conforming to UL 60947-4-1   65 kA Icu at 480 V AC 50/60 Hz conforming to UL 60947-4-1   10 kA Icu at 600 V AC 50/60 Hz conforming to UL 60947-4-1	
Performance level	H 70 kA 415 V AC	
Trip unit name	MicroLogic 2.2 M	
Trip unit technology	Electronic	
Trip unit protection functions	LSol	
Control type	Toggle	
Circuit breaker mounting mode	Fixed	

### Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz	
[Uimp] rated impulse withstand voltage	8 kV	

[Ics] rated service short-circuit breaking capacity	100 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 70 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2	
Mechanical durability	40000 cycles	
Electrical durability	40000 cycles at 440 V ln/2 20000 cycles at 440 V ln 15000 cycles at 690 V ln/2 7500 cycles at 690 V ln	
Power dissipation per pole	9.2 W	
Mounting support	Backplate	
Mounting position	Horizontal and vertical Flat on the back	
Upside connection	Front	
Downside connection	Front	
Connection pitch	35 mm	
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection	
Trip unit rating	150 A at 65 °C	
Motor tripping class	10 5 20	
Complementary motor protection	Phase unbalance	
Long-time pick-up adjustment	Adjustable 9 settings	
type Ir (thermal protection) [Ir] long-time protection pick-up	70150 A	
adjustment range	Fixed	
adjustment type tr [tr] long-time protection delay		
adjustment range	120 s at 1.5 x Ir for trip class 5 6.5 s at 6 x Ir for trip class 5 5 s at 7.2 x Ir for trip class 5 240 s at 1.5 x Ir for trip class 10 13.5 s at 6 x Ir for trip class 10 10 s at 7.2 x Ir for trip class 10 480 s at 1.5 x Ir for trip class 20 26 s at 6 x Ir for trip class 20 20 s at 7.2 x Ir for trip class 20	
Thermal memory	20 minutes before and after tripping	
Short-time protection pick-up adjustment type Isd	Adjustable 9 settings	
[Isd] Short-time protection pick- up adjustment range	513 x lr	
Short-time protection delay adjustment type tsd	Fixed	
Instantaneous protection pick-up adjustment type li	Fixed	
[li] instantaneous protection pick- up adjustment range	2250 A	
Earth-leakage protection	Without	
Zone selective interlocking ZSI	Without	
Number of slots for electrical auxiliaries	5 slot(s)	
Local signalling	Flashing LED (green) for ready to operate LED 95 % Ith (red) for temperature over set point	
Width (W)	105 mm	

Height (H)	161 mm
Depth (D)	86 mm
Net weight	2.2 kg

## Environment

Standards	EN/IEC 60947-2
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C
Relative humidity	095 %
Operating altitude	02000 m without derating 2000 m5000 m with derating

# Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	18.000 cm
Package 1 Length	19.000 cm
Package 1 Weight	1.943 kg
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	14.021 kg
Unit Type of Package 3	P12
Number of Units in Package 3	56
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	124.168 kg

## 🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	150
Environmental Disclosure	Product Environmental Profile

### **Use Better**

S Materials and Substances	
Recycled metal content at CR level	0
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
PVC free	Yes
Silicon free	No

### Use Longer

### $\circ$ Lifetime extension

Upgradeability	

No

### Use Again

$\circlearrowright$ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Product contains halogen above thresholds
Take-back	No