

# Product datasheet

Specifications



Circuit breaker, ComPacT  
NSX250N, 50kA/415VAC, 4 poles  
4D (neutral fully protected), TMD trip  
unit 160A

C25N4TM160

## Main

|                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPacT new generation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| product name                                         | ComPacT NSX new generation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Device short name                                    | NSX250N                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Product or component type                            | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Device application                                   | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Poles description                                    | 4P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Protected poles description                          | 4D                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Neutral position                                     | Left                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| [In] rated current                                   | 160 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Network type                                         | AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Utilisation category                                 | Category A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| [Icu] rated ultimate short-circuit breaking capacity | 90 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>85 kA Icu at 240 V AC 50/60 Hz conforming to UL 60947-4-1<br>50 kA Icu at 480 V AC 50/60 Hz conforming to UL 60947-4-1<br>15 kA Icu at 600 V AC 50/60 Hz conforming to UL 60947-4-1 |
| Performance level                                    | N 50 kA 415 V AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Trip unit name                                       | TM-D                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Trip unit technology                                 | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Trip unit protection functions                       | LI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Control type                                         | Toggle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## Complementary

|                                        |                   |
|----------------------------------------|-------------------|
| [Ui] rated insulation voltage          | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV              |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                                  |                                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[Ics] rated service short-circuit breaking capacity</b>       | 90 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>36 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| <b>Mechanical durability</b>                                     | 20000 cycles                                                                                                                                                                                                                                                                                                                                             |
| <b>Electrical durability</b>                                     | 20000 cycles at 440 V In/2<br>10000 cycles at 440 V In<br>10000 cycles at 690 V In/2<br>5000 cycles at 690 V In                                                                                                                                                                                                                                          |
| <b>Power dissipation per pole</b>                                | 11.78 W                                                                                                                                                                                                                                                                                                                                                  |
| <b>Mounting support</b>                                          | Backplate                                                                                                                                                                                                                                                                                                                                                |
| <b>Mounting position</b>                                         | Horizontal and vertical<br>Flat on the back                                                                                                                                                                                                                                                                                                              |
| <b>Upside connection</b>                                         | Front                                                                                                                                                                                                                                                                                                                                                    |
| <b>Downside connection</b>                                       | Front                                                                                                                                                                                                                                                                                                                                                    |
| <b>Connection pitch</b>                                          | 35 mm                                                                                                                                                                                                                                                                                                                                                    |
| <b>Protection type</b>                                           | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic)                                                                                                                                                                                                                                                                     |
| <b>Trip unit rating</b>                                          | 160 A at 40 °C                                                                                                                                                                                                                                                                                                                                           |
| <b>Long-time pick-up adjustment type Ir (thermal protection)</b> | Adjustable                                                                                                                                                                                                                                                                                                                                               |
| <b>[Ir] long-time protection pick-up adjustment range</b>        | 0.7...1 x In                                                                                                                                                                                                                                                                                                                                             |
| <b>Long-time protection delay adjustment type tr</b>             | Fixed                                                                                                                                                                                                                                                                                                                                                    |
| <b>[tr] long-time protection delay adjustment range</b>          | 120...400 s at 1.5 x In<br>15 s at 6 x Ir                                                                                                                                                                                                                                                                                                                |
| <b>Neutral protection settings</b>                               | 1 x Ir (4D)                                                                                                                                                                                                                                                                                                                                              |
| <b>Instantaneous protection pick-up adjustment type Ii</b>       | Fixed                                                                                                                                                                                                                                                                                                                                                    |
| <b>[Ii] instantaneous protection pick-up adjustment range</b>    | 1250 A                                                                                                                                                                                                                                                                                                                                                   |
| <b>Earth-leakage protection</b>                                  | Without                                                                                                                                                                                                                                                                                                                                                  |
| <b>Number of slots for electrical auxiliaries</b>                | 5 slot(s)                                                                                                                                                                                                                                                                                                                                                |
| <b>Width (W)</b>                                                 | 140 mm                                                                                                                                                                                                                                                                                                                                                   |
| <b>Height (H)</b>                                                | 161 mm                                                                                                                                                                                                                                                                                                                                                   |
| <b>Depth (D)</b>                                                 | 86 mm                                                                                                                                                                                                                                                                                                                                                    |
| <b>Net weight</b>                                                | 2.8 kg                                                                                                                                                                                                                                                                                                                                                   |

## Environment

|                                              |                              |
|----------------------------------------------|------------------------------|
| <b>Standards</b>                             | EN/IEC 60947-2               |
| <b>Overvoltage category</b>                  | Class II                     |
| <b>Electrical shock protection class</b>     | Class II                     |
| <b>Pollution degree</b>                      | 3 conforming to IEC 60664-1  |
| <b>IP degree of protection</b>               | IP40 conforming to IEC 60529 |
| <b>IK degree of protection</b>               | IK07 conforming to IEC 62262 |
| <b>Ambient air temperature for operation</b> | -25...70 °C                  |
| <b>Ambient air temperature for storage</b>   | -50...85 °C                  |

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| Relative humidity  | 0...95 %                                                     |
| Operating altitude | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 14 cm  |
| Package 1 Width              | 15 cm  |
| Package 1 Length             | 19 cm  |
| Package 1 Weight             | 2.5 kg |
| Unit Type of Package 2       | S03    |
| Number of Units in Package 2 | 6      |
| Package 2 Height             | 30 cm  |
| Package 2 Width              | 30 cm  |
| Package 2 Length             | 40 cm  |
| Package 2 Weight             | 15 kg  |

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

|  Environmental footprint |                                               |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)                                                     | 209                                           |
| Environmental Disclosure                                                                                  | <a href="#">Product Environmental Profile</a> |

Use Better

|  Materials and Substances |                                   |
|------------------------------------------------------------------------------------------------------------|-----------------------------------|
| Recycled metal content at CR level                                                                         | 0                                 |
| <a href="#">EU RoHS Directive</a>                                                                          | Compliant with Exemptions         |
| REACH Regulation                                                                                           | <a href="#">REACH Declaration</a> |
| PVC free                                                                                                   | Yes                               |

Use Again

|  Repack and remanufacture |                                                                                                                                                                                                                 |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circularity Profile                                                                                          | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| WEEE                                                                                                         |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance                                                                                  | Product contains halogen above thresholds                                                                                                                                                                       |
| Take-back                                                                                                    | No                                                                                                                                                                                                              |