

# Product datasheet

Specifications



trip unit MicroLogic 2.2 G for  
ComPacT NSX 160/250 circuit  
breakers, electronic, rating 160 A, 4  
poles 4d

C1642G160

EAN Code: 3606482000797

## Main

|                                |  |
|--------------------------------|--|
| Range                          | ComPacT new generation   |
| Range of product               | ComPacT NSX100...250   |
| Product or component type      | Trip unit  |
| Trip unit name                 | MicroLogic 2.2 G   |
| Trip unit technology           | Electronic   |
| Range compatibility            | ComPacT NSX160<br>ComPacT NSX250   |
| Device application             | Generator  |
| Poles description              | 4P   |
| Protected poles description    | 3D + N/2<br>4D<br>3D   |
| Neutral position               | Left   |
| Trip unit protection functions | LSol   |
| Protection type                | L : for overload protection (long time)<br>So : for short time short-circuit protection with fixed delay<br>I : for instantaneous short-circuit protection |
| Trip unit rating               | 160 A at 40 °C   |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz  |
| Network type                   | AC   |
| Network frequency              | 50/60 Hz   |
| Circuit breaker mounting mode  | Fixed  |

## Complementary

|   |   |
|---|---|
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings                                     |
| [Ir] long-time protection pick-up adjustment range        | 63...160 A  |
| Long-time protection delay adjustment type tr             | Fixed   |
| [tr] long-time protection delay adjustment range          | 15 s at 1.5 x Ir<br>0.35 s at 7.2 x Ir<br>0.5 s at 6 x Ir |
| Neutral protection settings                               | 0.5 x Ir (3D + N/2)<br>1 x Ir (4D)<br>No protection (3D)  |
| Thermal memory  | 20 minutes before and after tripping                      |
| Short-time protection pick-up adjustment type Isd         | Adjustable  |

|   |   |
|---|---|
| <b>[Isd] Short-time protection pick-up adjustment range</b>   | 1.5...9 x Ir  |
| <b>Short-time protection delay adjustment type tsd</b>        | Fixed   |
| <b>Instantaneous protection pick-up adjustment type li</b>    | Fixed   |
| <b>[Ii] instantaneous protection pick-up adjustment range</b> | 2400 A  |
| <b>Earth-leakage protection</b>                               | Without   |
| <b>Zone selective interlocking ZSI</b>                        | Without   |
| <b>Local signalling</b>                                       | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload |

## Environment

|  |                              |
|--|------------------------------|
| <b>Standards</b>                             | EN/IEC 60947-2               |
| <b>Electrical shock protection class</b>     | Class II                     |
| <b>Pollution degree</b>                      | 3 conforming to IEC 60947-1  |
| <b>IP degree of protection</b>               | IP40 conforming to IEC 60529 |
| <b>Ambient air temperature for operation</b> | -25...70 °C                  |
| <b>Ambient air temperature for storage</b>   | -50...85 °C                  |

## Packing Units

|                                     |           |
|-------------------------------------|-----------|
| <b>Unit Type of Package 1</b>       | PCE       |
| <b>Number of Units in Package 1</b> | 1         |
| <b>Package 1 Height</b>             | 6.5 cm    |
| <b>Package 1 Width</b>              | 9.5 cm    |
| <b>Package 1 Length</b>             | 16.0 cm   |
| <b>Package 1 Weight</b>             | 564.0 g   |
| <b>Unit Type of Package 2</b>       | S03       |
| <b>Number of Units in Package 2</b> | 18        |
| <b>Package 2 Height</b>             | 30.0 cm   |
| <b>Package 2 Width</b>              | 30.0 cm   |
| <b>Package 2 Length</b>             | 40.0 cm   |
| <b>Package 2 Weight</b>             | 10.608 kg |

## Logistical informations

|                          |    |
|--------------------------|----|
| <b>Country of origin</b> | FR |
|--------------------------|----|

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 36

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Recycled metal content at CR level 0

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Halogen content performance Product contains halogen above thresholds

PVC free Yes

Silicon free No

## Use Longer

### Lifetime extension

Upgradeability No

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins