

Product datasheet

Specifications



trip unit TM200G for ComPacT NSX
250 circuit breakers, thermal
magnetic, rating 200 A, 3 poles 3d

C253MG200

EAN Code: 3606482000568

Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250
Product or component type	Trip unit
Trip unit name	TM-G
Trip unit technology	Thermal-magnetic
Range compatibility	ComPacT NSX250 ComPacT NSX250 DC
Device application	Generator
Poles description	3P
Protected poles description	3D
Trip unit protection functions	LI
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	200 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz 750 V DC
Network type	AC DC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

Complementary

Long-time pick-up adjustment type I_r (thermal protection)	Adjustable
[I_r] long-time protection pick-up adjustment range	0.7...1 x I_n
Long-time protection delay adjustment type t_r	Fixed
[t_r] long-time protection delay adjustment range	120...400 s at 1.5 x I_n
Instantaneous protection pick-up adjustment type I_i	Fixed
[I_i] instantaneous protection pick-up adjustment range	440 A
Earth-leakage protection	Without

Environment

Standards	EN/IEC 60947-2
Electrical shock protection class	Class II

Pollution degree	3 conforming to IEC 60947-1
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.000 cm
Package 1 Width	10.000 cm
Package 1 Length	12.000 cm
Package 1 Weight	433.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	32
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	14.276 kg
Unit Type of Package 3	P12
Number of Units in Package 3	256
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	126.208 kg

Logistical informations

Country of origin	CN
--------------------------	----

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **107**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level **0**

[EU RoHS Directive](#) **Compliant with Exemptions**

REACH Regulation [REACH Declaration](#)

Halogen content performance **Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**

WEEE  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**