

Earth-leakage add-on alarm module VigiPacT, ComPacT NSX 400/630, 200VAC to 440VAC, 30mA to 30A, 3 poles

LV432469

Main

Range of product	ComPacT NSX400630 ComPact NSX400630	
Device short name	VigiPacT	
Product or component type	Vigi add-on	
Device application	Wiring	
Range compatibility	ComPacT ComPacT NSX400 circuit breaker ComPacT ComPacT NSX630 circuit breaker ComPact ComPact NSX400 circuit breaker ComPact ComPact NSX630 circuit breaker	
Poles description	3P	
[In] rated current	400 A 630 A	
Earth-leakage protection class	Class A Class AC	
Residual earth-leakage sensitity adjustment type	Adjustable	
Earth-leakage sensitivity	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 1 A for class A 3 A for class A 10 A for class AC	

Complementary

Network type	AC	
Network frequency	50/60 Hz	
[Ue] rated operational voltage	200440 V AC 50/60 Hz conforming to IEC 60947-2	
Earth-leakage protection	Without	
Maximum breaking time	800 ms	
Overvoltage category	IV	

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	14.200 cm
Package 1 Width	17.300 cm
Package 1 Length	19.700 cm
Package 1 Weight	2.664 kg
Unit Type of Package 2	S03
Number of Units in Package 2	3
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.454 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint		
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	41	
Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances	
Recycled metal content at CR level	0
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
Silicon free	No

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins