



SIMATIC S7-1200, Analog input, SM 1231 RTD, 4xAI RTD module

Figure similar

General information	
Product type designation	SM 1231, AI 4x16 bit RTD
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	40 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4; Resistance thermometer
permissible input voltage for voltage input (destruction limit), max.	±35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
• Voltage	No
• Current	No
• Thermocouple	No
• Resistance thermometer	Yes; Resistance-type transmitter: Pt10, Pt50, Pt100, Pt200, Pt500, Pt1000, Ni100, Ni120, Ni200, Ni500, Ni1000, Cu10, Cu50, Cu100, LG-Ni1000
• Resistance	Yes; 150 Ω, 300 Ω, 600 Ω
Input ranges (rated values), resistance thermometer	
• Cu 10	Yes
— Input resistance (Cu 10)	10 Ω
• Ni 100	Yes
— Input resistance (Ni 100)	100 Ω
• Ni 1000	Yes
— Input resistance (Ni 1000)	1 000 Ω
• LG-Ni 1000	Yes
— Input resistance (LG-Ni 1000)	1 000 Ω
• Ni 120	Yes
— Input resistance (Ni 120)	120 Ω
• Ni 200	Yes
— Input resistance (Ni 200)	200 Ω
• Ni 500	Yes
— Input resistance (Ni 500)	500 Ω
• Pt 100	Yes
— Input resistance (Pt 100)	100 Ω
• Pt 1000	Yes
— Input resistance (Pt 1000)	1 000 Ω

<ul style="list-style-type: none"> • Pt 200 <ul style="list-style-type: none"> — Input resistance (Pt 200) 	Yes 200 Ω
<ul style="list-style-type: none"> • Pt 500 <ul style="list-style-type: none"> — Input resistance (Pt 500) 	Yes 500 Ω
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> • 0 to 150 ohms 	Yes
<ul style="list-style-type: none"> • 0 to 300 ohms 	Yes
<ul style="list-style-type: none"> • 0 to 600 ohms 	Yes
Thermocouple (TC)	
Temperature compensation	
<ul style="list-style-type: none"> — parameterizable 	No
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	15 bit; + sign
<ul style="list-style-type: none"> • Integration time, parameterizable 	No
<ul style="list-style-type: none"> • Interference voltage suppression for interference frequency f_1 in Hz 	85 dB at 50 / 60 / 400 Hz
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C ±0.1%, to 55 °C ±0.2% total measurement range
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.05 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
<ul style="list-style-type: none"> • Common mode interference, min. 	120 dB
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes; Can be read out
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage 	Yes
<ul style="list-style-type: none"> • Wire-break 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • for status of the inputs 	Yes
<ul style="list-style-type: none"> • for maintenance 	Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ecological footprint	
<ul style="list-style-type: none"> • environmental product declaration 	Yes
Global warming potential	
<ul style="list-style-type: none"> — global warming potential, (total) [CO2 eq] 	43.1 kg
<ul style="list-style-type: none"> — global warming potential, (during production) [CO2 eq] 	7.62 kg
<ul style="list-style-type: none"> — global warming potential, (during operation) [CO2 eq] 	36 kg
<ul style="list-style-type: none"> — global warming potential, (after end of life cycle) [CO2 eq] 	-0.544 kg
Ambient conditions	
Free fall	
<ul style="list-style-type: none"> • Fall height, max. 	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	-20 °C
<ul style="list-style-type: none"> • max. 	60 °C

• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C

Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C

Air pressure acc. to IEC 60068-2-13	
• Operation, min.	795 hPa
• Operation, max.	1 080 hPa
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa

Relative humidity	
• Operation at 25 °C without condensation, max.	95 %

Pollutant concentrations	
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free

connection method	
required front connector	Yes

Mechanics/material	
Enclosure material (front)	
• Plastic	Yes

Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm

Weights	
Weight, approx.	220 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
	IDEA	4	3562
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval	EMV
---------------------------------	------------

[Miscellaneous](#)

[Manufacturer Declaration](#)



For use in hazardous locations

Marine / Shipping

Environment

[CCC-Ex](#)



last modified:

10/9/2024

