

product type designation



CM 1542-5

communications module CM 1542-5 for connection of S7-1500 to PROFIBUS DP, DP-V1 master or DP Device, S7 and PG/OP communication, data record routing, time-of-day synchronization, diagnostics.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS 	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS 	1
type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / according to PROFIBUS 	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	15 V
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 15 V 	3 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 15 V / typical 	0.2 A
power loss [W]	3 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation for horizontally arranged busbars / during operation during storage during transport note 	-30 ... +40 °C -30 ... +60 °C -40 ... +70 °C -40 ... +70 °C without condensation or icing
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	restrictions for installation altitudes > 2 000 m, see manual
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1500 single width
width	35 mm
height	142 mm
depth	129 mm
net weight	0.4 kg
fastening method	
<ul style="list-style-type: none"> S7-1500 rail mounting 	Yes

product features, product functions, product components / general

number of units	8
<ul style="list-style-type: none"> per CPU / maximum 	depending on CPU type
<ul style="list-style-type: none"> note 	

performance data / open communication

number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	30
data volume	240 byte
<ul style="list-style-type: none"> as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	

performance data / PROFIBUS DP

service / as DP master	Yes
<ul style="list-style-type: none"> DPV1 	
number of DP slaves	125
<ul style="list-style-type: none"> on DP master / operable 	
data volume	8192 byte
<ul style="list-style-type: none"> of the address range of the inputs / as DP master / total of the address range of the outputs / as DP master / total of the address range of the inputs / per DP slave of the address range of the outputs / per DP slave 	8192 byte 8192 byte 244 byte 244 byte
service / as DP slave	Yes
<ul style="list-style-type: none"> DPV0 DPV1 	Yes Yes
data volume	240 byte
<ul style="list-style-type: none"> of the address range of the inputs / as DP slave / total of the address range of the outputs / as DP slave / total 	240 byte 240 byte

performance data / S7 communication

number of possible connections / for S7 communication	48; depending on the system upper limit
<ul style="list-style-type: none"> maximum 	

performance data / multi-protocol mode

number of active connections / with multi-protocol mode	48
---	----

performance data / telecontrol

protocol / is supported	No
<ul style="list-style-type: none"> TCP/IP 	

product functions / management, configuration, engineering

configuration software	STEP 7 Professional V18 (TIA Portal) or higher
<ul style="list-style-type: none"> required 	
identification & maintenance function	Yes
<ul style="list-style-type: none"> I&M0 - device-specific information I&M1 - higher level designation/location designation 	Yes Yes

product functions / diagnostics

product function / web-based diagnostics	Yes; via S7-1500 CPU
--	----------------------

product functions / time

product function / pass on time synchronization	Yes
---	-----

standards, specifications, approvals

reference code	KEC
<ul style="list-style-type: none"> according to IEC 81346-2:2019 	

standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	115.52 kg
<ul style="list-style-type: none"> total during manufacturing during operation after end of life 	21.24 kg 93.93 kg 0.35 kg

further information / internet links

internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to website: Industrial communication to web page: SiePortal to website: Image database 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb

- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://siemens.com/cax>

<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval	For use in hazardous locations	Environment
		 

last modified:

2/28/2025 