



CJ1W-ID262

Digital input unit, 64 x 24 VDC inputs, MIL40 connector (not included)

Specifications

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	64
Digital input type	PNP/NPN
Permitted voltage at input	20.4-26.4 V
OFF/ON delay	0-32 ms
Number of digital outputs	0
Digital output type	None
Output current	0 A
Short-circuit protected outputs	✗
I/O connection type	MIL (plug not included)
Number of I/O connectors	2
Detachable I/O connector	✓
Suitable for safety functions	✗
Number of IOV (V+) terminals	0
Number of IOG (V-) terminals	0
Number of COM terminals	8
Product Height (unpacked)	90 mm
Product Width (unpacked)	31 mm
Product Depth (unpacked)	83.6 mm
Product Weight (unpacked)	96 g

Accessories



G70V-SID16P

Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals



G70V-SID16P-1

Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals

P2RV-4-100IMC

G2RV interface cable for use between CJ1W-ID233/ID262 and 4 P2RV-8-I-F modules, 1 m

P2RV-4-200IMC

G2RV interface cable for use between CJ1W-ID233/ID262 and 4 P2RV-8-I-F modules, 2 m



P2RVC-8ST-I-5

Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Input, 8 channels, NPN, 30 VAC/DC, Total 2 A, Push-in



P2RVC-8ST-I-5-1

Interface unit for G2RV-SR/G3RV-ST Push-in, PLC Input, 8 channels, PNP, 30 VAC/DC, Total 2 A, Push-in



P2RVC-8ST-I-7-1

Interface unit for G2RV-SR/G3RV-ST Screw, PLC Input, 8 channels, PNP, 30 VAC/DC, Total 2 A, Rising-up screw



XW2D-40G6

General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points



XW2K-40G-O32C

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



XW2Z-0030FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 0.3 m



XW2Z-0050FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 0.5 m



XW2Z-0100FF-L

I/O connection cable, unshielded, MIL40 to MIL40, 1 m

	XW2Z-0100FH-L02	I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m
	XW2Z-0100FN-L	I/O connection cable, unshielded, MIL40 to open ends, 1 m
	XW2Z-0150FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 1.5 m
	XW2Z-0150FN-L	I/O connection cable, unshielded, MIL40 to open ends, 1.5 m
	XW2Z-0200FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 2 m
	XW2Z-0200FH-L02	I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m
	XW2Z-0200FN-L	I/O connection cable, unshielded, MIL40 to open ends, 2 m
	XW2Z-0300FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 3 m
	XW2Z-0300FH-L02	I/O connection cable, unshielded, MIL40 to 2 x MIL20, 3 m
	XW2Z-0300FN-L	I/O connection cable, unshielded, MIL40 to open ends, 3 m
	XW2Z-0500FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 5 m
	XW2Z-0500FN-L	I/O connection cable, unshielded, MIL40 to open ends, 5 m
	XW2Z-100K	I/O connection cable, MIL40 to MIL40, 1 m
	XW2Z-150K	I/O connection cable, MIL40 to MIL40, 1.5 m

	XW2Z-200K	I/O connection cable, MIL40 to MIL40, 2 m
	XW2Z-300K	I/O connection cable, MIL40 to MIL40, 3 m
	XW2Z-500K	I/O connection cable, MIL40 to MIL40, 5 m
	XW2Z-C50K	I/O connection cable, MIL40 to MIL40, 0.5 m
	XW2Z-RO100-75-D1	I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 1 m
	XW2Z-RO200-175-D1	I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 2.0 m and 1.75 m
	XW2Z-RO75-50-D1	I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 0.75 m

Downloads

CAD Library



CJ1W-ID/IA **Datasheet**

EN PDF 3.36 MB



CJ2 CPU Units Hardware **Users Manual**

EN PDF 8.4 MB



CJ2-Series **Programmable** **Controller** **Datasheet**

EN PDF 17.9 MB



EAC Mark removal **Discontinuation Notice**

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 29 May, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://industrial.omron.eu)