



CJ1W-OD232

Digital output unit, 32 x transistor outputs, PNP, 0.5 A, 24 VDC, load short-circuit protection, MIL40 connector (not included)

Specifications

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	0
Digital input type	None
OFF/ON delay	2-8 ms
Number of digital outputs	32
Digital output type	PNP
Permitted voltage at output	20.4-26.4 V
Output current	0.5 A
Short-circuit protected outputs	✗
I/O connection type	MIL (plug not included)
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
Number of IOV (V+) terminals	2
Number of IOG (V-) terminals	2
Number of COM terminals	0
Product Height (unpacked)	90 mm
Product Width (unpacked)	20 mm
Product Depth (unpacked)	83.6 mm
Product Weight (unpacked)	70 g

	G70A-ZOC16-4 DC24	Output Terminal Block for Relay or SSR, 16-point, for PNP output units
	G70V-SOC16P-1	Relay terminal, PLC Output, 16 channels, PNP, Push-in terminals
	P2RV-4-100C	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 1 m
	P2RV-4-200C	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 2 m
	P2RV-4-300C	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 3 m
	XW2D-40G6	General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points
	XW2K-40G-O32C	PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting
	XW2Z-0030FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 0.3 m
	XW2Z-0050FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 0.5 m
	XW2Z-0100FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 1 m
	XW2Z-0100FH-L02	I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m
	XW2Z-0100FN-L	I/O connection cable, unshielded, MIL40 to open ends, 1 m

	XW2Z-0150FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 1.5 m
	XW2Z-0150FN-L	I/O connection cable, unshielded, MIL40 to open ends, 1.5 m
	XW2Z-0200FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 2 m
	XW2Z-0200FH-L02	I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m
	XW2Z-0200FN-L	I/O connection cable, unshielded, MIL40 to open ends, 2 m
	XW2Z-0300FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 3 m
	XW2Z-0300FH-L02	I/O connection cable, unshielded, MIL40 to 2 x MIL20, 3 m
	XW2Z-0300FN-L	I/O connection cable, unshielded, MIL40 to open ends, 3 m
	XW2Z-0500FF-L	I/O connection cable, unshielded, MIL40 to MIL40, 5 m
	XW2Z-0500FN-L	I/O connection cable, unshielded, MIL40 to open ends, 5 m
	XW2Z-100K	I/O connection cable, MIL40 to MIL40, 1 m
	XW2Z-150K	I/O connection cable, MIL40 to MIL40, 1.5 m
	XW2Z-200K	I/O connection cable, MIL40 to MIL40, 2 m
	XW2Z-300K	I/O connection cable, MIL40 to MIL40, 3 m



XW2Z-500K

I/O connection cable, MIL40 to MIL40, 5 m



XW2Z-C50K

I/O connection cable, MIL40 to MIL40, 0.5 m



XW2Z-RO100-75-D1

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 1 m



XW2Z-RO200-175-D1

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 2.0 m and 1.75 m



XW2Z-RO75-50-D1

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 0.75 m

Downloads

CAD Library



CJ1W-OC/OA/OD
Datasheet

EN PDF 3.98 MB



CJ2 CPU Units Hardware
Users Manual

EN PDF 8.4 MB



CJ2-Series
Programmable
Controller
Datasheet

EN PDF 17.9 MB



EAC Mark removal
Discontinuation Notice

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 25 May, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)