




CJ1W-OD261

Digital output unit, 64 x transistor outputs, NPN, 0.5 A, 12 to 24 VDC, 2 x FCN40 connectors (not included)

Specifications

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	0
Digital input type	None
Number of digital outputs	64
Digital output type	NPN
Permitted voltage at output	10.2-26.4 V
Output current	0.3 A
Short-circuit protected outputs	✗
I/O connection type	FCN (plug not included)
Number of I/O connectors	2
Detachable I/O connector	✓
Suitable for safety functions	✗
Number of IOV (V+) terminals	8
Number of IOG (V-) terminals	8
Number of COM terminals	0
Product Height (unpacked)	90 mm
Product Width (unpacked)	31 mm
Product Depth (unpacked)	66.5 mm
Product Weight (unpacked)	110 g

Accessories

	G70A-ZOC16-3 DC24	Output Terminal Block for Relay or SSR, 16-point, for NPN output units
	XW2D-40G6	General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points
	XW2K-40G-O32B	PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting
	XW2K-40G-O32B-OUT	PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Output, Signal: 0.5 A, Power: 7 A, NPN, 30 VDC, DIN rail horizontal and vertical mounting
	XW2Z-0100BF-L	I/O connection cable, unshielded, FCN40 to MIL40, 1 m
	XW2Z-0100BH-L02	I/O connection cable, unshielded, FCN40 to 2 x MIL20, 1 m, cross-wired
	XW2Z-0100BN-L	I/O connection cable, unshielded, FCN40 to open ends, 1 m
	XW2Z-0200BF-L	I/O connection cable, unshielded, FCN40 to MIL40, 2 m
	XW2Z-0200BH-L02	I/O connection cable, unshielded, FCN40 to 2 x MIL20, 2 m, cross-wired
	XW2Z-0200BN-L	I/O connection cable, unshielded, FCN40 to open ends, 2 m
	XW2Z-0300BN-L	I/O connection cable, unshielded, FCN40 to open ends, 3 m
	XW2Z-050B	I/O connection cable, FCN40 to MIL40, 0.5 m
	XW2Z-100B	I/O connection cable, FCN40 to MIL40, 1 m

	XW2Z-150B	I/O connection cable, FCN40 to MIL40, 1.5 m
	XW2Z-200B	I/O connection cable, FCN40 to MIL40, 2 m
	XW2Z-300B	I/O connection cable, FCN40 to MIL40, 3 m
	XW2Z-RO100C-75	I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 1 m / 0.75 m
	XW2Z-RO150C-125	I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 1.5 m / 1.25 m
	XW2Z-RO200C-150	I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 2 m / 1.5 m
	XW2Z-RO200C-175	I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70 A-ZOC16-3, 2 m / 1.75 m

Downloads

CAD Library



CJ1W-OC/OA/OD Datasheet

EN PDF 3.98 MB



CJ2 CPU Units Hardware Users Manual

EN PDF 8.4 MB



CJ2-Series **Programmable** **Controller** Datasheet

EN PDF 17.9 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB

