



NB10W-TW01B-V1

Touch screen HMI, 10.1 inch WSVGA (1024 x 600 pixel), TFT color, Ethernet + USB Host

Specifications

Screen diagonal	10.1 in
Number of pixels, horizontal	1024
Number of pixels, vertical	600
Type of display	TFT
Frame color	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colors of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	268.8 mm
Height of the front	210.8 mm
Width of panel cutout	258 mm
Height of panel cutout	200 mm
Built-in depth	54 mm
Product Weight (unpacked)	1465 g



NB10W-KBA04

Accessory HMI, protective sheets for NB10W (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



How to Import PLC Variables from Sysmac Studio

Practice Guide

EN PDF 534 KB



Maxell CR-series button cells

Battery Safety Datasheet

EN PDF 132 KB



NB Faceplate 4.0 - Multilanguage Software

EN ZIP 89.1 MB



NB Series Programmable Terminal Brochure

EN PDF 4.06 MB



NB-Designer Setup v1.5.3.1

Software

EN ZIP 374 MB



NB-Designer Setup v1.6.4.0

Software

EN ZIP 430 MB



NB-Series Getting Started Guide

EN PDF 10 MB



NB-Series Setup Manual

EN PDF 6.08 MB



NB-Series Host Connection

Setup Manual

EN PDF 21.3 MB