



NX-AD3204

4 Analog Inputs, 4 to 20 mA differential, resolution 1:8000, 250 μ s/ch, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Analog I/O
Number of analog inputs	4
Temperature input type	None
Linear analog input type	4 to 20 mA
Resolution of the analog inputs	13 Bit
Input circuit type	Differential
Number of analog outputs	0
Linear analog output type	None
Resolution of the analog outputs	0 Bit
Conversion time	1 ms/unit
Signal processing	Free running
IO-Link master	✗
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	70 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

Spare parts



NX-TBA122

Replacement screwless push-in connector with 12 wiring terminals (marked A+B)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



NX-series Analog I/O Unit - NX-AD/DA Datasheet

EN PDF 5.68 MB



NX-series Analog I/O Units Users Manual

EN PDF 7.31 MB



NX-series I/O system Brochure

EN PDF 8.37 MB



Omron GX-JC0x-x EtherCAT Junction Box EtherCAT ESI file

EN ZIP 3.36 KB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 29 May, 2025. Click here for [terms of use](#).