



NX-EC0122

1 x Incremental Encoder PNP Input, Phases A and B: Single-phase 500 kHz (phase difference pulse Input x4: 125 kHz),
Phase Z: 125 kHz, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Encoder input
Digital input type	Incremental encoder, PNP
Digital output type	None
Signal processing	Free running, Synchronous, Task period prioritized
Number of encoder input channels	1
Max. encoder input frequency	500 kHz
Number of pulse output channels	0
Max. pulse output frequency	0 kHz
IO-Link master	✗
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	70 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

Spare parts



NX-TBA162

Replacement screwless push-in connector with 16 wiring terminals (marked A+B)

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 7.5 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



NX-series Reference Manual

EN PDF 1.45 MB



NX-series I/O system Brochure

EN PDF 8.37 MB



NX-series Position Interface Unit Datasheet

EN PDF 6.82 MB



NX-series Position Interface Units Users Manual

EN PDF 18.4 MB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB