



R88M-1M75030T-BS2

1S AC servo motor, 750 W, 230 VAC, 3000 rpm, 2.39 Nm, absolute encoder, with brake

Specifications

Servo control method	EtherCAT
Drive supply voltage	230 V single phase
Rated output	0.75 kW
Rated speed	3000 r/min
Rated torque	2.39 Nm
Peak torque	8.4 Nm
Encoder type	Absolute without battery
Encoder resolution	23 Bit
Motor with brake	✓
Motor with oil seal	✗
Flange size square (LC)	80 mm
Shaft diameter	19 mm
Shaft with key	✓
Shaft with tap	✓
Product Weight (unpacked)	3900 g



R88D-1SN08H-ECT

1S servo drive, EtherCAT type, 800 W, 1~ 230 VAC



R88D-1SN08H-ECT-51

1S-51 servo drive with STO, SS1 and SLS safety, EtherCAT type, 750 W, 1 or 3? 230 VAC

Accessories



R88A-CA1A001-5BF-E

1S series servo brake cable, 1.5 m, 230 V: 100 to 750 W



R88A-CA1A001-5SF-E

1S series servo motor power cable, 1.5 m, 230 V: 100 to 750 W



R88A-CA1A003BF-E

1S series servo brake cable, 3 m, 230 V: 100 to 750 W



R88A-CA1A003SF-E

1S series servo motor power cable, 3 m, 230 V: 100 to 750 W



R88A-CA1A005BF-E

1S series servo brake cable, 5 m, 230 V: 100 to 750 W




R88A-CA1A005SF-E

1S series servo motor power cable, 5 m, 230 V: 100 to 750 W



R88A-CA1A010BF-E

1S series servo brake cable, 10 m, 230 V: 100 to 750 W

	R88A-CA1A010SF-E	1S series servo motor power cable, 10 m, 230 V: 100 to 750 W
	R88A-CA1A015BF-E	1S series servo brake cable, 15 m, 230 V: 100 to 750 W
	R88A-CA1A015SF-E	1S series servo motor power cable, 15 m, 230 V: 100 to 750 W
	R88A-CA1A020BF-E	1S series servo brake cable, 20 m, 230 V: 100 to 750 W
	R88A-CA1A020SF-E	1S series servo motor power cable, 20 m, 230 V: 100 to 750 W
	R88A-CR1A001-5CF-E	1S series servo encoder cable, 1.5m, 230V: 50-750W
	R88A-CR1A003CF-E	1S series servo encoder cable, 3m, 230V: 50-750W
	R88A-CR1A005CF-E	1S series servo encoder cable, 5m, 230V: 50-750W
	R88A-CR1A010CF-E	1S series servo encoder cable, 10m, 230V: 50-750W
	R88A-CR1A015CF-E	1S series servo encoder cable, 15m, 230V: 50-750W
	R88A-CR1A020CF-E	1S series servo encoder cable, 20m, 230V: 50-750W
	R88A-SC011S-E	1S series cable clamp A. Used in 230 V drives up to 750 W

CAD Library



1S Series Users Manual

EN PDF 23 MB



1S Series - Expanded with high capacity range: 4 - 15 kW Flyer

EN PDF 1.64 MB



1S Series Incremental Encoder Type Users Manual

EN PDF 6.34 MB



1S Series Multi-axis Setup and Tuning Getting Started Guide

EN PDF 7.86 MB



1S Servo System Brochure

EN PDF 25.5 MB



1S-series Servos Instruction Manual

EN PDF 5.63 MB



AC Servomotor_Servo Drives - Replace Guide Replacement guide

EN PDF 4.74 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Motor Sizing Tool Operation Manual

EN PDF 3.83 MB



R88M-1 1S-series Servo Motor Datasheet

EN PDF 1.57 MB



Redundancy and Motion Safety Flyer

EN PDF 960 KB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB



Using R88A-CA1G power cables Technical Information

EN PDF 1.6 MB



motor_sizing_tool_v1.80.1.16 Configurator

EN ZIP 36.1 MB