



## S8VS-12024A

Power supply, 120 W, 100 to 240 VAC input, 24VDC 5A output, DIN rail mounting, digital display with running voltage and current, peak current, and maintenance monitor function with settable alarm point

# Specifications

|                                  |                      |
|----------------------------------|----------------------|
| Type                             | DIN-rail             |
| Mounting method                  | DIN rail             |
| Phase                            | Single               |
| Power output                     | 120 W                |
| Efficiency                       | 85 %                 |
| Output voltage                   | 24 V                 |
| Rated output current             | 5 A                  |
| Temperature range                | -10-60 °C            |
| Terminal type                    | Screw                |
| Communication port(s)            | None                 |
| Alarm function                   | Transistor - sinking |
| Number of output branches        | 1                    |
| Rated supply voltage at AC 50 Hz | 100-240 V            |
| Allowable supply voltage AC      | 85-264 V             |
| Allowable supply voltage DC      | 80-370 V             |
| Product Width (unpacked)         | 50 mm                |
| Product Height (unpacked)        | 115 mm               |
| Product Depth (unpacked)         | 121.3 mm             |

CAD Library



## EAC Mark removal Discontinuation Notice

EN PDF 221 KB



## S8VS Switch Mode Power Supply Datasheet

EN PDF 5.86 MB