

PSTX570-690-70



PSTX570-690-70 Softstarter



General Information

Global Commercial Alias	PSTX570-690-70
Extended Product Type	PSTX570-690-70
Product ID	1SFA898217R7000
ABB Type Designation	PSTX570-690-70
EAN	7320500508978
Catalog Description	PSTX570-690-70 Softstarter
Long Description	Softstarter PSTX570-690-70 for max 690V main voltage and 100 - 250V 50/60Hz control supply voltage.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044090

Popular Downloads

Data Sheet, Technical Information	1SFC132009C0201
Instructions and Manuals	1SFC132081M0201

Dimensions

Product Net Width	361 mm
Product Net Height	493 mm
Product Net Depth / Length	282 mm
Product Net Weight	25 kg

Technical

Rated Operational Voltage	Main Circuit 208 ... 690 V AC
Rated Control Supply Voltage (U_s)	100 ... 250 V
Rated Control Circuit Voltage (U_c)	DC Operation 24 V
Rated Operational Power - In-Line Connection (P_e)	(400 V) 315 kW
Rated Operational Current - In-Line Connection (I_e)	570 A
Rated Operational Power - Inside Delta Connection	at 400 V 540 kW
Rated Operational Current - Inside Delta Connection	987 A
Integrated Electronic Overload	Yes

Initial Voltage During Start	10 ... 99 %
Product Main Type	PSTX570

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMT005209
Environmental Information	2CMT005232
Instructions and Manuals	1SFC132081M0201

Categories

Drives → Softstarters → Softstarters → PSTX Softstarters

