



K8DT-LS1CA

Monitoring relay 17.5 mm wide, Conductive level control for liquid, 10k to 100k Ohm, 1 x SPDT, 100-240 VAC

Specifications

Application	Ordinary purified water, Sewage water
Functions	Conductive level control
Cable length	100 m
Installation type	DIN rail
Terminal type	Push-in
Size	17.5 mm
Supply voltage AC	100-240 V
Output type	Relay
Contact description	SPDT
Body color	Black
Number of inputs for electrodes	3

Accessories

	BF-1	Electrode holder, 1-pole electrode, standard type (150°C), liquid with low specific resistance
	BF-3	Electrode holder, 3 way, standard type (150°C)
	BF-5	Electrode holder, 5 way, standard type (150°C)
	BS-1	Electrode holder, 1-pol electrode, for high pressure or high temperature applications (250°C), 1.96Mpa
	F03-11 PROTECTIVE COVER FOR BF	Protective cover for electrode holders PS or BF series)

	F03-12	PS Electrode Holder Mounting Plate
	F03-14 1P SEPARATOR	Electrode separator, 1 electrode, ceramic, 250 °C max, 15 g
	F03-14 3P SEPARATOR	Electrode separator, 3 electrodes, ceramic, 250 °C max, 30 g
	F03-14 5P SEPARATOR	Electrode separator, 5 electrodes, ceramic, 250 °C max, 30 g
	F03-60 SUS316 ELECTRODE SET	Set including F03-01 SUS316 electrode, F03-02 SUS316 connecting nuts, F03-03 SUS316 lock nuts
	PH-2 HAIPREN CODE 20M	Underwater Electrode, Hypalon cable, double pole, 20 m length
	PS-31 SUS304 1000MM	Electrode set, holder & electrodes, 1 m length, 4 mm diameter, non-extendable
	PS-31 SUS304 300MM	Electrode set, holder & electrodes, 0.3 m length, 4 mm diameter, non-extendable
	PS-3S	Electrode holder, 3 way
	PS-4S	Electrode holder, 4 way
	PS-5S	Electrode holder, 5 way
	Y92A-D1A	Plastic cover for H3DT & K8DT

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



K8DT-LS Conductive Level Controller Datasheet

EN PDF 3.06 MB



Panel Building Brochure

EN PDF 3.11 MB