

Bulletin 700-HA

Plug-in Style Relays

Type Designation / Contact Ratings

700-HA	3	3	Z2	-	3	-	4
Relays Bulletin			Coil Control Voltage				
DC					Options		
Contact Type 3 - Standard contact AgNi B - Twin contacts AgNi X - Twin contacts AgNi, 10 µm gold plated			DC Z06 - 6VDC Z12 - 12 VDC Z24 - 24 VDC Z36 - 36 VDC Z48 - 48 VDC Z60 - 60 VDC Z1 - 110 VDC Z01 - 125 VDC Z3 - 140 VDC Z2 - 220 VDC		- Blank No special features - 3 Push to test & manual override - 4 Pilot light (not available for "A27" coil) - 4L Pilot light (for use with coil voltages "A2") - 3- 4 Push to test & manual override W / pilot light -3- 4L Push to test & manual override W / pilot light (for use with coil voltages "A2") -99 Bulk pack (10 pieces)		
No. of Changeover Switches 2 - 2 Changeover contacts 3 - 3 Changeover contacts			AC A06 - 6 VAC 50/60Hz A12 - 12 VAC 50/60Hz A24 - 24 VAC 50/60Hz A36 - 36 VAC 50/60Hz A48 - 48 VAC 50/60Hz A11 - 110 VAC 50/60Hz A1 - 120 VAC 50/60Hz A03 - 230 VAC 50/60Hz A2 - 240 VAC 50/60Hz A27 - 277 VAC 50/60Hz		Remarks: < 80 V with LED > 80 V mit neon lamp Mechanical switching position indications included in scope of delivery as standard		